APD1400BD

POWER
YOUR
FUTURE


1400 kVA / 1120 kW

DIESEL GENERATING SET 400/230 V - 50 Hz

MODEL			APD1400BD
Power Pf. 0.8	Standby	kVA	1400
		kW	1120
	Prime	kVA	1270
		kW	1016

Standby: Continuous running at variable load for duration of an emergency. No overload is permitted on these ratings. In accordance with ISO 3046.
Prime: Continuous running at variable load for unlimited periods with 10% overload available for 1 hour in any 12 hours period. In accordance with ISO 8528, ISO 3046.

- ✓ High quality, reliable and complete power unit
- ✓ Compact design
- ✓ Easy start and maintenance possibility
- ✓ Every generating set is subject to a comprehensive test program which includes full load testing, checking and provision of all control and safety shut down functions testing
- ✓ Fully engineered with a wide range of options and accessories: Canopy, soundproof canopy and off-road trailer



ISO 9001 ISO 14001 ISO 45001 ISO 10002 ISO 27001 CE

Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice



ENGINE

BAUDOUIN		
Model		12M33G1400/5
Engine Power Output at rated rpm	kWm	1210
	HP	1623
Aspiration and Cooling		Turbocharged and Aftercooled
Total Displacement	Litre	39.2
No. of Cylinders and Build		12 - Vee
Engine Speed	rpm	1500
Bore and Stroke	mmxmm	150x185
Compression Ratio		15:1
Governor		Electronic
Fuel Consumption at full load	L/hr	258.6
Fuel Tank Capacity	Litre	OPEN：N/A / CANOPY：1500
Oil Capacity	Litre	160
Coolant Capacity	Litre	272
Radiator Cooling Air	m^3/min	2280
Air Intake – Engine	m^3/min	82.1
Exhaust Gas Flow	m^3/min	277.2

- ✓ Heavy duty diesel engine
- ✓ Four stroke, water cooled, Turbocharged and Aftercooled
- ✓ Direct injection fuel system
- ✓ Electronic Governor system
- ✓ 12/24 V D.C. starter and charge alternator
- ✓ Replaceable fuel filter, oil filter and dry element air filter
- ✓ Cooling radiator and fan
- ✓ Starter battery (with lead acid) including Rack and Cables
- ✓ Flexible fuel connection hoses and manual oil sump drain valve
- ✓ Industrial capacity exhaust silencer and steel bellows
- ✓ Jacket water heater(at automatic models)
- ✓ Operation manuals and circuit diagram documents

ALTERNATOR

Design	Brushless single bearing, revolving field
Stator	2/3 pitch
Rotor	Single bearing, flexible disc
Insulation System	Class H
Standard Temperature Rise	125 - 163° C Continuous
Exciter Type	PMG
Phase Rotation	A (U), B (V), C (W)
Alternator Cooling	Direct drive centrifugal blower fan
AC Waveform Total Harmonic Distortion	Non distorting balanced linear load < 5%
Telephone Influence Factor (TIF)	<50 per NEMA MG1-32
Telephone Harmonic Factor (THF)	<2%

- ✓ Brushless, single bearing system, flexible disc, 4 poles
- ✓ Insulation class H
- ✓ Standard degree of protection IP22 (*IP23 is available.)
- ✓ Self-exciting and self-regulating
- ✓ Impregnation with tropicalized epoxy varnish
- ✓ Solid state Automatic Voltage Regulator
- ✓ Stator winding with 2/3 pitch for improved harmonics

CONTROL SYSTEM

Control supervision and protection panel is mounted on the genset base frame. The control panel is equipped as follows:



DSE 7320

1. Auto Mains Failure Control Panel

Panel equipment:

- ✓ Control with AMF module
- ✓ Static battery charger
- ✓ Emergency stop push button

a) Generating set control module DSE 7320 features:

- ✓ The module is used to monitor a mains supply and starts and stops a standby generating set
- ✓ Micro-processor based design
- ✓ Automatic control of mains and generator contactors
- ✓ Monitors engine performance and AC power output
- ✓ LED alarm indication
- ✓ Front panel configuration of timers and alarm trip points
- ✓ Easy push button control
  STOP/RESET – MANUAL – TEST – AUTO - MUTE ALARM - START

b) Metering via LED display:

- ✓ Generator Volts (L-L / L-N)
- ✓ Engine oil pressure (PSI-Bar)
- ✓ Generator Ampere (L1,L2,L3)
- ✓ Engine temperature (° C&° F)
- ✓ Generator Frequency (Hz)
- ✓ Plant battery volts
- ✓ Engine hours run
- ✓ Mains Volts (Ph-Ph / Ph-N)
- ✓ Generator kVA, kWh
- ✓ Generator kW as % of rated kW setting
- ✓ Generator Cos (σ)

c) Alarms:

- ✓ Over and Under Speed
- ✓ Low and High Battery Volt.
- ✓ Start and Stop Failure
- ✓ Charge fail
- ✓ Over Current
- ✓ Under / Over Generator Voltage
- ✓ Low Oil Pressure
- ✓ Emergency stop
- ✓ High engine temperature
- ✓ kW overload
- ✓ Unbalanced load
- ✓ Independent earth fault trip

d) LED indications

Four configurable LED's like:

- ✓ Mains available
- ✓ Generator available
- ✓ Mains on load
- ✓ Generator on load

OPTIONAL EQUIPMENTS

Diesel Engine

- ✓ Oil heater

Alternator

- ✓ 3/4 Pole Output Circuit Breaker
- ✓ Anti-condensation Heater


Panel


- ✓ Charge ammeter
- ✓ Transfer Switch 3 Pole
- ✓ Transfer Switch 4 Pole
- ✓ Earth Fault, single set

Accessories

- ✓ Bulk fuel tank
- ✓ Automatic filling system
- ✓ Fuel-water separator filter
- ✓ Low fuel level alarm
- ✓ Residential silencer
- ✓ Enclosure or sound-proof canopy
- ✓ Trailer
- ✓ Manual oil drain pump
- ✓ Tool kit for maintenance

CHASSIS







- ✓ The complete gen-set is mounted as whole on a heavy-duty fabricated, steel base frame
- ✓ Anti-vibration pads are fixed between the engine/alternator feet and the base frame
- ✓ Base frame design incorporates an integral fuel tank (Up to 1000 kVA)
- ✓ The generating set can be lifted or carefully pushed / pulled by the base frame
- ✓ Dial type fuel gauge and drain plug on the fuel tank
- ✓ Forklift pockets within base frame (Up to 500 kVA)

DIMENSIONS

OPEN TYPE		
DIMENSIONS (LxWxH)	mm	4772x1970x2552
DRY WEIGHT	kg	8500
SOUND ATTENUATED TYPE		
DIMENSIONS (L×W×H)	mm	7528x2302x3420
DRY WEIGHT	kg	12300

CANOPY





- ✓ All canopy parts are designed with modular principles
- ✓ Without welding assembly
- ✓ Doors on each side
- ✓ All metal canopy parts are painted by electrostatic polyester powder paint
- ✓ Exhaust silencer is protected against environment influences
- ✓ Thermally insulated engine exhaust system
- ✓ Emergency stop push button is installed outside of the canopy
- ✓ Easy lifting and moving
- ✓ Easy maintenance and operation

Aksa Power Generation (China) Co., Ltd
Add: No.19 Tongjiang North Road, Changzhou New District, Changzhou / China
Tel: +86 (0)519 8515 0205 E-mail: INTLsales@aksapowergen.com
www.aksapowergen.com
Aksa Power Generation is a member of KAZANCI HOLDING www.aksa.com.tr

Publication No 2026/09/14